



Pipeline Tracer Wire - Type PTW 60°C/600V

Description & Features:

UL listed Pipeline Tracer Wire is a solid copper conductor insulated with a poly compound that provides excellent abrasion, crush, chemical, oil and moisture resistance.

- UL Listed for Direct Burial
- Moisture resistant
- Chemical, oil resistant
- Impact, crush and abrasion resistant

Application:

- Suitable for direct burial with or within plastic pipe to facilitate the detection and tracing of underground piping systems

Construction:

Conductor: Soft annealed solid copper per ASTM B-3

Insulation: Yellow, Poly

Temperature: 60° C dry and wet

Voltage: 600 volts

Specifications & Standards:

UL listed as miscellaneous wire

RoHS Compliant

Type PTW - Pipeline Tracer Wire 60°C/600V

Part Number	Conductor		Nominals (In.)		Color	Standard Length		Product Wgt. (Lbs./Mft.)
	AWG	Strands	Insulation	O.D.		Put-up	Ship Pkg.	
TRACE14YW	14	Solid	0.45	.154	Yellow	1,000' Reel	1,000	18
TRACE12YW	12	Solid	0.45	.171	Yellow	1,000' Reel	1,000	26
TRACE10YW	10	Solid	0.45	.192	Yellow	1,000' Reel	1,000	38

All diameters are nominal values; all weights are exclusive of packaging. All diameters and weights are subject to normal manufacturing tolerances.

All sales are subject to Standard Terms & Conditions of Sale.

2009